

Bdiscom Srl Milan (I)

Your experienced partner for Plasma power supplies

BDS SP 500 DC Sputter Power Supply



Bdiscom power supply for DC sputter processes. 500 Watt F.S.

Highly price competitive DC power supply with fast arc detection (< 200 nSec) and digital interfaces. Suitable for small and medium R/D and industrial sputter tools

www.bdiscom.com

info@bdiscom.it

BDS SP 500 Sputter Power Supply

Introduction:

Bdiscom DC power supply for Sputtering processes. High efficiency, reliability with the Most attractive price available in the market place.

Some highlights:

500 Watt F.S. (1000 Volt output), equipped with user friendly Active Touch Screen display (AFP).

Power requirements	230V - 1PH±10%
Weight	About 5 Kg
Dimensions	132.5 x 241 x 400 (mm)
Regulation mode	Power, Voltage, Current
Max power output	500 Watt F.S.
Output Voltage	1000 Volt DC max
Output Current	1 Amp
Arc Handling Detection	< 200 nSec
Interfaces	A/D, RS 232 Included (Profibus Option)
Cooling	Forced Air
Operating Temperature	5-40 ° C
Efficiency	> 90 %
Display	Touch panel 240x128 pixel

EMC classification according to EN 55011:

This is a ISM (industrial scientific medical) Equipment and it is EN 55011 group 2, class A compliant.

CE MARK

BDISCOM SRL Tel: (+39) 0382 926987 – Fax: (+39) 0382 923070 www.bdiscom.com info@bdiscom.it

